

Revision Equivalence for Ranking Functions

Alexander Hahn

joint work with Gabriele Kern-Isberner, Jonas Haldimann, and Christoph Beierle

Department of Computer Science
Technische Universität Dortmund, Germany


Cape-KR 2025 @ Cape Town, South Africa
February 10–14

Motivation: Total Preorders

Total Preorders (TPOs) over possible worlds are widely used in *non-monotonic reasoning* (NMR) and *belief revision* (BR).


Motivation: Total Preorders

Total Preorders (TPOs) over possible worlds are widely used in *non-monotonic reasoning* (NMR) and *belief revision* (BR).



Motivation: Total Preorders

Total Preorders (TPOs) over possible worlds are widely used in *non-monotonic reasoning* (NMR) and *belief revision* (BR).




NMR

inference relations based on TPOs
guarantee KLM postulates
mentioned by Lucas :)

Motivation: Total Preorders

Total Preorders (TPOs) over possible worlds are widely used in *non-monotonic reasoning* (NMR) and *belief revision* (BR).



NMR

inference relations based on TPOs
guarantee KLM postulates
mentioned by Lucas :)

BR

revision operators based on TPOs satisfy
AGM & DP postulates
mentioned by Clayton :)

Motivation: Conditionals

Total preorders over possible worlds essentially encode **conditional information**.

Motivation: Conditionals


Total preorders over possible worlds essentially encode **conditional information**.

Ω	A	B	C	...
ω_1	0	0	0	
ω_2	0	0	1	
ω_3	0	1	0	
ω_4	0	1	1	
ω_5	1	0	0	
ω_6	1	0	1	
ω_7	1	1	0	
ω_8	1	1	1	

Motivation: Conditionals

Total preorders over possible worlds essentially encode **conditional information**.

Ω	A	B	C	...
ω_1	0	0	0	
ω_2	0	0	1	
ω_3	0	1	0	
ω_4	0	1	1	
ω_5	1	0	0	
ω_6	1	0	1	
ω_7	1	1	0	
ω_8	1	1	1	




Motivation: Conditionals

Total preorders over possible worlds essentially encode **conditional information**.

Ω	A	B	C	...
ω_1	0	0	0	
ω_2	0	0	1	
ω_3	0	1	0	
ω_4	0	1	1	
ω_5	1	0	0	
ω_6	1	0	1	
ω_7	1	1	0	
ω_8	1	1	1	

Total Preorder
over Ω



Models of $A \wedge B$

Models of $A \wedge \neg B$

Models of $\neg A$

Motivation: Conditionals

Total preorders over possible worlds essentially encode **conditional information**.

Ω	A	B	C	...
ω_1	0	0	0	
ω_2	0	0	1	
ω_3	0	1	0	
ω_4	0	1	1	
ω_5	1	0	0	
ω_6	1	0	1	
ω_7	1	1	0	
ω_8	1	1	1	

Total Preorder
over Ω

Plausibility
↓

ω_4 ω_6
ω_3 ω_5 ω_8
ω_2 ω_7
ω_1

Models of $A \wedge B$

Models of $A \wedge \neg B$

Models of $\neg A$

\Rightarrow **Conditional:** $(B|A)$ meaning “If A, then (usually/plausibly) B”.
(since $A \wedge B$ is more plausible than $A \wedge \neg B$)

Motivation: Ranking Functions

Total Preorder over Ω :

$\omega_4 \ \omega_6$
$\omega_3 \ \omega_5 \ \omega_8$
$\omega_2 \ \omega_7$
ω_1

Motivation: Ranking Functions

~~Total Preorder over Ω :~~

Ordinal Conditional Function (OCF) over Ω :

3	$\omega_4 \omega_6$
2	$\omega_3 \omega_5 \omega_8$
1	$\omega_2 \omega_7$
0	ω_1

Motivation: Ranking Functions

~~Total Preorder over Ω :~~

Ordinal Conditional Functions (OCFs) over Ω :

3	$\omega_4 \omega_6$
2	$\omega_3 \omega_5 \omega_8$
1	$\omega_2 \omega_7$
0	ω_1

4	$\omega_4 \omega_6$
3	$\omega_3 \omega_5 \omega_8$
2	$\omega_2 \omega_7$
1	
0	ω_1

Motivation: Ranking Functions

~~Total Preorder over Ω :~~

Ordinal Conditional Functions (OCFs) over Ω :

3	$\omega_4 \omega_6$
2	$\omega_3 \omega_5 \omega_8$
1	$\omega_2 \omega_7$
0	ω_1

4	$\omega_4 \omega_6$
3	$\omega_3 \omega_5 \omega_8$
2	$\omega_2 \omega_7$
1	
0	ω_1

5	$\omega_4 \omega_6$
4	
3	$\omega_3 \omega_5 \omega_8$
2	$\omega_2 \omega_7$
1	
0	ω_1

Motivation: Ranking Functions

~~Total Preorder over Ω :~~

Ordinal Conditional Functions (OCFs) over Ω :

3	$\omega_4 \omega_6$
2	$\omega_3 \omega_5 \omega_8$
1	$\omega_2 \omega_7$
0	ω_1

4	$\omega_4 \omega_6$
3	$\omega_3 \omega_5 \omega_8$
2	$\omega_2 \omega_7$
1	
0	ω_1

5	$\omega_4 \omega_6$
4	
3	$\omega_3 \omega_5 \omega_8$
2	$\omega_2 \omega_7$
1	
0	ω_1

9	$\omega_4 \omega_6$
8	
7	$\omega_3 \omega_5 \omega_8$
6	
5	
4	
3	
2	$\omega_2 \omega_7$
1	
0	ω_1

Motivation: Ranking Functions

~~Total Preorder over Ω :~~

Ordinal Conditional Functions (OCFs) over Ω :

3	$\omega_4 \omega_6$
2	$\omega_3 \omega_5 \omega_8$
1	$\omega_2 \omega_7$
0	ω_1

\approx

4	$\omega_4 \omega_6$
3	$\omega_3 \omega_5 \omega_8$
2	$\omega_2 \omega_7$
1	
0	ω_1

\approx

5	$\omega_4 \omega_6$
4	
3	$\omega_3 \omega_5 \omega_8$
2	$\omega_2 \omega_7$
1	
0	ω_1

\approx

9	$\omega_4 \omega_6$
8	
7	$\omega_3 \omega_5 \omega_8$
6	
5	
4	
3	
2	$\omega_2 \omega_7$
1	
0	ω_1

Motivation: Ranking Functions

~~Total Preorder over Ω :~~

Ordinal Conditional Functions (OCFs) over Ω :

3	$\omega_4 \omega_6$
2	$\omega_3 \omega_5 \omega_8$
1	$\omega_2 \omega_7$
0	ω_1

\approx

4	$\omega_4 \omega_6$
3	$\omega_3 \omega_5 \omega_8$
2	$\omega_2 \omega_7$
1	
0	ω_1

\approx

5	$\omega_4 \omega_6$
4	
3	$\omega_3 \omega_5 \omega_8$
2	$\omega_2 \omega_7$
1	
0	ω_1

\approx

9	$\omega_4 \omega_6$
8	
7	$\omega_3 \omega_5 \omega_8$
6	
5	
4	
3	
2	$\omega_2 \omega_7$
1	
0	ω_1

Open Questions:

Motivation: Ranking Functions

~~Total Preorder over Ω :~~

Ordinal Conditional Functions (OCFs) over Ω :

3	$\omega_4 \omega_6$
2	$\omega_3 \omega_5 \omega_8$
1	$\omega_2 \omega_7$
0	ω_1

\approx

4	$\omega_4 \omega_6$
3	$\omega_3 \omega_5 \omega_8$
2	$\omega_2 \omega_7$
1	
0	ω_1

\approx

5	$\omega_4 \omega_6$
4	
3	$\omega_3 \omega_5 \omega_8$
2	$\omega_2 \omega_7$
1	
0	ω_1

\approx

9	$\omega_4 \omega_6$
8	
7	$\omega_3 \omega_5 \omega_8$
6	
5	
4	
3	
2	$\omega_2 \omega_7$
1	
0	ω_1

Open Questions:

- Which ranking function would be *most adequate* to represent the total preorder?

Motivation: Ranking Functions

~~Total Preorder over Ω :~~

Ordinal Conditional Functions (OCFs) over Ω :

3	$\omega_4 \omega_6$
2	$\omega_3 \omega_5 \omega_8$
1	$\omega_2 \omega_7$
0	ω_1

\approx

4	$\omega_4 \omega_6$
3	$\omega_3 \omega_5 \omega_8$
2	$\omega_2 \omega_7$
1	
0	ω_1

\approx

5	$\omega_4 \omega_6$
4	
3	$\omega_3 \omega_5 \omega_8$
2	$\omega_2 \omega_7$
1	
0	ω_1

\approx

9	$\omega_4 \omega_6$
8	
7	$\omega_3 \omega_5 \omega_8$
6	
5	
4	
3	
2	$\omega_2 \omega_7$
1	
0	ω_1

Open Questions:

- Which ranking function would be *most adequate* to represent the total preorder?
- And when *does it matter* which ranking representation we choose?

Motivation: Empty Layers during Revision

Empty (in-between) layers in OCFs show their power during *belief change* operations.

5	
4	
3	$\omega_7^{-A} \omega_8^A$
2	$\omega_4^A \omega_5^{-A} \omega_6^A$
1	$\omega_2^A \omega_3^{-A}$
0	ω_1^{-A}

vs.

5	
4	$\omega_7^{-A} \omega_8^A$
3	$\omega_4^A \omega_5^{-A} \omega_6^A$
2	
1	$\omega_2^A \omega_3^{-A}$
0	ω_1^{-A}

Motivation: Empty Layers during Revision

Empty (in-between) layers in OCFs show their power during *belief change* operations.

5	
4	
3	$\omega_7^{-A} \omega_8^A$
2	$\omega_4^A \omega_5^{-A} \omega_6^A$
1	$\omega_2^A \omega_3^{-A}$
0	ω_1^{-A}

vs.

5	
4	$\omega_7^{-A} \omega_8^A$
3	$\omega_4^A \omega_5^{-A} \omega_6^A$
2	
1	$\omega_2^A \omega_3^{-A}$
0	ω_1^{-A}

Motivation: Empty Layers during Revision

Empty (in-between) layers in OCFs show their power during *belief change* operations.

5	
4	
3	$\omega_7^{-A} \omega_8^A$
2	$\omega_4^A \omega_5^{-A} \omega_6^A$
1	$\omega_2^A \omega_3^{-A}$
0	ω_1^{-A}

vs.


5	
4	$\omega_7^{-A} \omega_8^A$
3	$\omega_4^A \omega_5^{-A} \omega_6^A$
2	
1	$\omega_2^A \omega_3^{-A}$
0	ω_1^{-A}

Scenario: Revision by A

- ⇒ Models of A become more plausible (rank -1).
- ⇒ Models of $\neg A$ become less plausible (rank $+1$).

Motivation: Empty Layers during Revision

Empty (in-between) layers in OCFs show their power during *belief change* operations.




Scenario: Revision by A

- ⇒ Models of A become more plausible (rank -1).
- ⇒ Models of $\neg A$ become less plausible (rank $+1$).

Motivation: Empty Layers during Revision

Empty (in-between) layers in OCFs show their power during *belief change* operations.




Scenario: Revision by A

- \Rightarrow Models of A become more plausible (rank -1).
- \Rightarrow Models of $\neg A$ become less plausible (rank $+1$).

Motivation: Empty Layers during Revision

Empty (in-between) layers in OCFs show their power during *belief change* operations.



Scenario: Revision by A

- \Rightarrow Models of A become more plausible (rank -1).
- \Rightarrow Models of $\neg A$ become less plausible (rank $+1$).

Revision Equivalence

- Idea: $\kappa_1 * A \cong \kappa_2 * A$ for all A .
- \Rightarrow **Representation Invariance**

Overview

- 1 Introduction
- 2 Epistemic States and AGM-based Iterated Revision
- 3 Transformations between TPOs and OCFs
- 4 Revision Equivalence for OCFs
- 5 How to achieve Revision Equivalence? (← I will probably skip this)
- 6 Conclusion

Formal Basics

Propositional Logic

- Σ : signature containing atomic propositions, i.e. $\Sigma = \{a, b, c, \dots\}$.
- \mathcal{L} : propositional language over signature Σ .
- Ω : set of propositional interpretations (*possible worlds*) over Σ .
- $\omega \models A$ iff $A \in \mathcal{L}$ holds in $\omega \in \Omega$.
- $Mod(A) := \{\omega \in \Omega \mid \omega \models A\}$.

Conditionals

- Language: $(\mathcal{L}|\mathcal{L}) := \{(B|A) \mid A, B \in \mathcal{L}\}$
- $(B|A)$ formalizes: “If A , then *usually* B .”

Epistemic States

Epistemic States [Darwiche & Pearl, 1997]

In the Darwiche-Pearl Framework of iterated revision, an epistemic state Ψ is represented by a *total preorder* (TPO) \preceq_{Ψ} over a set of possible worlds Ω .

- $\omega_1 \preceq_{\Psi} \omega_2$ iff the possible world $\omega_1 \in \Omega$ is at least as plausible as $\omega_2 \in \Omega$ in Ψ .
- $\Psi \models (B|A)$ iff at least one possible world satisfying $A \wedge B$ is more plausible than all worlds satisfying $A \wedge \neg B$.

Epistemic States

Epistemic States [Darwiche & Pearl, 1997]

In the Darwiche-Pearl Framework of iterated revision, an epistemic state Ψ is represented by a *total preorder* (TPO) \preceq_{Ψ} over a set of possible worlds Ω .

- $\omega_1 \preceq_{\Psi} \omega_2$ iff the possible world $\omega_1 \in \Omega$ is at least as plausible as $\omega_2 \in \Omega$ in Ψ .
- $\Psi \models (B|A)$ iff at least one possible world satisfying $A \wedge B$ is more plausible than all worlds satisfying $A \wedge \neg B$.

Properties of Total Preorders

Technically, \preceq_{Ψ} is a relation $\preceq_{\Psi} \subseteq \Omega \times \Omega$ with the following properties:

- 1 $\omega_1 \preceq_{\Psi} \omega_2$ or $\omega_2 \preceq_{\Psi} \omega_1$ holds. (Totality)
- 2 $\omega_1 \preceq_{\Psi} \omega_2$ and $\omega_2 \preceq_{\Psi} \omega_3$ imply $\omega_1 \preceq_{\Psi} \omega_3$. (Transitivity)

for all $\omega_1, \omega_2, \omega_3 \in \Omega$.

DP-style Iterated Revision

Proposition [Darwiche & Pearl, 1997]

A revision operator $*$ that assigns a posterior epistemic state $\Psi * A$ to a prior state Ψ and a proposition A is an *AGM revision operator for epistemic states* iff there exists a *total preorder* (TPO) \preceq_Ψ on Ω with $Mod(Bel(\Psi)) = \min(\Omega, \preceq_\Psi)$ such that

$$Mod(Bel(\Psi * C)) = \min(Mod(C), \preceq_\Psi)$$

holds for every proposition C .

DP-style Iterated Revision

Proposition [Darwiche & Pearl, 1997]

A revision operator $*$ that assigns a posterior epistemic state $\Psi * A$ to a prior state Ψ and a proposition A is an *AGM revision operator for epistemic states* iff there exists a *total preorder (TPO)* \preceq_Ψ on Ω with $Mod(Bel(\Psi)) = \min(\Omega, \preceq_\Psi)$ such that

$$Mod(Bel(\Psi * C)) = \min(Mod(C), \preceq_\Psi)$$

holds for every proposition C .

$\omega_7^{\neg A}$ ω_8^A
ω_4^A $\omega_5^{\neg A}$ ω_6^A
ω_2^A $\omega_3^{\neg A}$
$\omega_1^{\neg A}$

← ω_2 : most plausible world after revision by A

← ω_1 : most plausible world (currently)

Example Revision Operators for TPOs

Natural Revision [Boutilier, 1993]

The *natural revision operator* \bullet_n is defined by the following condition:

$$\omega \preceq_{\Psi \bullet_n A} \omega' \quad \text{iff} \quad \begin{array}{l} (1) \ \omega \in \min(\text{Mod}(A), \preceq_{\Psi}), \text{ or} \\ (2) \ \omega, \omega' \notin \min(\text{Mod}(A), \preceq_{\Psi}) \text{ and } \omega \preceq_{\Psi} \omega'. \end{array}$$

Example Revision Operators for TPOs

Natural Revision [Boutilier, 1993]

The *natural revision operator* \bullet_n is defined by the following condition:

$$\omega \preceq_{\Psi \bullet_n A} \omega' \quad \text{iff} \quad \begin{aligned} &(1) \omega \in \min(\text{Mod}(A), \preceq_{\Psi}), \text{ or} \\ &(2) \omega, \omega' \notin \min(\text{Mod}(A), \preceq_{\Psi}) \text{ and } \omega \preceq_{\Psi} \omega'. \end{aligned}$$

→ “pull down” minimal models of A (and keep relative order between other worlds)

Example Revision Operators for TPOs

Natural Revision [Boutilier, 1993]

The *natural revision operator* \bullet_n is defined by the following condition:

$$\omega \preceq_{\Psi \bullet_n A} \omega' \quad \text{iff} \quad \begin{array}{l} (1) \omega \in \min(\text{Mod}(A), \preceq_{\Psi}), \text{ or} \\ (2) \omega, \omega' \notin \min(\text{Mod}(A), \preceq_{\Psi}) \text{ and } \omega \preceq_{\Psi} \omega'. \end{array}$$

→ “pull down” minimal models of A (and keep relative order between other worlds)

Lexicographic Revision [Nayak, Pagnucco, Peppas, 2003]

The *lexicographic revision operator* \bullet_{ℓ} is defined by the following condition:

$$\omega \preceq_{\Psi \bullet_{\ell} A} \omega' \quad \text{iff} \quad \begin{array}{l} (1) \omega \models A \text{ and } \omega' \not\models A, \text{ or} \\ (2) (\omega \models A \text{ iff } \omega' \models A) \text{ and } \omega \preceq_{\Psi} \omega'. \end{array}$$

Example Revision Operators for TPOs

Natural Revision [Boutilier, 1993]

The *natural revision operator* \bullet_n is defined by the following condition:

$$\omega \preceq_{\Psi \bullet_n A} \omega' \quad \text{iff} \quad \begin{array}{l} (1) \omega \in \min(\text{Mod}(A), \preceq_{\Psi}), \text{ or} \\ (2) \omega, \omega' \notin \min(\text{Mod}(A), \preceq_{\Psi}) \text{ and } \omega \preceq_{\Psi} \omega'. \end{array}$$

→ “pull down” minimal models of A (and keep relative order between other worlds)

Lexicographic Revision [Nayak, Pagnucco, Peppas, 2003]

The *lexicographic revision operator* \bullet_{ℓ} is defined by the following condition:

$$\omega \preceq_{\Psi \bullet_{\ell} A} \omega' \quad \text{iff} \quad \begin{array}{l} (1) \omega \models A \text{ and } \omega' \not\models A, \text{ or} \\ (2) (\omega \models A \text{ iff } \omega' \models A) \text{ and } \omega \preceq_{\Psi} \omega'. \end{array}$$

→ “pull down” all models of A (and keep relative order within models/non-models)

Ranking Functions

Definition: Ordinal Conditional Function [Spohn, 1988]

An *ordinal conditional function* (OCF) or *ranking function* is a mapping

$$\kappa : \Omega \rightarrow \mathbb{N} \cup \{\infty\}$$

with $\kappa^{-1}(0) \neq \emptyset$.

Ranking Functions

Definition: Ordinal Conditional Function [Spohn, 1988]

An *ordinal conditional function* (OCF) or *ranking function* is a mapping

$$\kappa : \Omega \rightarrow \mathbb{N} \cup \{\infty\}$$

with $\kappa^{-1}(0) \neq \emptyset$.

The rank of a formula A is given by $\kappa(A) = \min\{\kappa(\omega) \mid \omega \models A\}$.

The acceptance relation w.r.t. conditionals is defined by

$$\kappa \models (B|A) \quad \text{iff} \quad \kappa(A \wedge B) < \kappa(A \wedge \neg B).$$

(\implies OCFs can be considered an implementation of total preorders.)

Ranking Functions

Definition: Ordinal Conditional Function [Spohn, 1988]

An *ordinal conditional function* (OCF) or *ranking function* is a mapping

$$\kappa : \Omega \rightarrow \mathbb{N} \cup \{\infty\}$$

with $\kappa^{-1}(0) \neq \emptyset$.

The rank of a formula A is given by $\kappa(A) = \min\{\kappa(\omega) \mid \omega \models A\}$.

The acceptance relation w.r.t. conditionals is defined by

$$\kappa \models (B|A) \quad \text{iff} \quad \kappa(A \wedge B) < \kappa(A \wedge \neg B).$$

(\implies OCFs can be considered an implementation of total preorders.)

Inferential Equivalence $\kappa \cong \kappa'$: $\kappa(\omega_1) \leq \kappa(\omega_2)$ iff $\kappa'(\omega_1) \leq \kappa'(\omega_2)$ for all $\omega_1, \omega_2 \in \Omega$.

Strategic c-Revisions for OCFs

c-Revisions for OCFs [Kern-Isberner, 2004]

Let κ be an OCF and $\Delta = \{(B_1|A_1), \dots, (B_n|A_n)\}$ a set of conditionals. Then a *c-revision of κ by Δ* is an OCF $\kappa^* = \kappa * \Delta$ of the form

$$\kappa^*(\omega) = \kappa_0 + \kappa(\omega) + \sum_{\substack{1 \leq i \leq n \\ \omega \models A_i \wedge \neg B_i}} \eta_i$$

with nonnegative integers $\eta_i \in \mathbb{N}$ for each $(B_i|A_i)$ ensuring that $\kappa^* \models \Delta$,

Strategic c-Revisions for OCFs

c-Revisions for OCFs [Kern-Isberner, 2004]

Let κ be an OCF and $\Delta = \{(B_1|A_1), \dots, (B_n|A_n)\}$ a set of conditionals. Then a *c-revision of κ by Δ* is an OCF $\kappa^* = \kappa * \Delta$ of the form

$$\kappa^*(\omega) = \kappa_0 + \kappa(\omega) + \sum_{\substack{1 \leq i \leq n \\ \omega \models A_i \wedge \neg B_i}} \eta_i$$

with nonnegative integers $\eta_i \in \mathbb{N}$ for each $(B_i|A_i)$ ensuring that $\kappa^* \models \Delta$,
 \longrightarrow The rank of a world ω is shifted by a sum of “penalties” for falsifying conditionals.

Strategic c-Revisions for OCFs

c-Revisions for OCFs [Kern-Isberner, 2004]

Let κ be an OCF and $\Delta = \{(B_1|A_1), \dots, (B_n|A_n)\}$ a set of conditionals. Then a *c-revision of κ by Δ* is an OCF $\kappa^* = \kappa * \Delta$ of the form

$$\kappa^*(\omega) = \kappa_0 + \kappa(\omega) + \sum_{\substack{1 \leq i \leq n \\ \omega \models A_i \wedge \neg B_i}} \eta_i$$


with nonnegative integers $\eta_i \in \mathbb{N}$ for each $(B_i|A_i)$ ensuring that $\kappa^* \models \Delta$,
 \longrightarrow The rank of a world ω is shifted by a sum of “penalties” for falsifying conditionals.

Selection Strategies [Kern-Isberner, Sezgin, Beierle, 2022]

A *selection strategy* is a mapping $\sigma : (\kappa, \Delta) \mapsto \vec{\eta}$ where $\vec{\eta}$ is a solution to the constraints above.


Transformations between TPOs and OCFs

[Kern-Isberner, Sezgin, Beierle, 2022]




Transformations between TPOs and OCFs

[Kern-Isberner, Sezgin, Beierle, 2022]




Transformations between TPOs and OCFs

[Kern-Isberner, Sezgin, Beierle, 2022]



Transformations between TPOs and OCFs

[Kern-Isberner, Sezgin, Beierle, 2022]



Note: $\tau \circ \rho = id$, but $\rho \circ \tau \neq id$ in general.

Example: Transformations

Let a ranking function κ be defined as:

3	ω_4
2	
1	$\omega_2 \ \omega_3$
0	ω_1

Example: Transformations

Let a ranking function κ be defined as:

3	ω_4
2	
1	$\omega_2 \ \omega_3$
0	ω_1



Then $\tau(\kappa)$ returns the following TPO Ψ_κ :

$$\omega_1 \prec \omega_2 \approx \omega_3 \prec \omega_4$$

Example: Transformations

Let a ranking function κ be defined as:

3	ω_4
2	
1	$\omega_2 \ \omega_3$
0	ω_1



Then $\tau(\kappa)$ returns the following TPO Ψ_κ :

$$\omega_1 \prec \omega_2 \approx \omega_3 \prec \omega_4$$



Now $\rho(\Psi_\kappa)$ returns κ_{Ψ_κ} :


2	ω_4
1	$\omega_2 \ \omega_3$
0	ω_1

Motivation: Revision Equivalence


5	
4	
3	$\omega_7^{-A} \omega_8^A$
2	$\omega_4^A \omega_5^{-A} \omega_6^A$
1	$\omega_2^A \omega_3^{-A}$
0	ω_1^{-A}

5	
4	$\omega_7^{-A} \omega_8^A$
3	$\omega_4^A \omega_5^{-A} \omega_6^A$
2	
1	$\omega_2^A \omega_3^{-A}$
0	ω_1^{-A}

Motivation: Revision Equivalence



Motivation: Revision Equivalence



We want to preserve equivalence of OCFs during revision.

Revision Equivalence

Let $*$ be an iterated revision operator for OCFs, taking (sets of) propositions resp. conditionals as input.

- κ_1, κ_2 are *(propositionally) revision equivalent with respect to $*$* if $\kappa_1 * A \cong \kappa_2 * A$ for all $A \in \mathcal{L}$.

Revision Equivalence

Let $*$ be an iterated revision operator for OCFs, taking (sets of) propositions resp. conditionals as input.

- κ_1, κ_2 are *(propositionally) revision equivalent with respect to $*$*
if $\kappa_1 * A \cong \kappa_2 * A$ for all $A \in \mathcal{L}$.
- κ_1, κ_2 are *conditionally revision equivalent with respect to $*$*
if $\kappa_1 * (B|A) \cong \kappa_2 * (B|A)$ for all $(B|A) \in (\mathcal{L}|\mathcal{L})$.

Revision Equivalence

Let $*$ be an iterated revision operator for OCFs, taking (sets of) propositions resp. conditionals as input.

- κ_1, κ_2 are *(propositionally) revision equivalent with respect to $*$*
if $\kappa_1 * A \cong \kappa_2 * A$ for all $A \in \mathcal{L}$.
- κ_1, κ_2 are *conditionally revision equivalent with respect to $*$*
if $\kappa_1 * (B|A) \cong \kappa_2 * (B|A)$ for all $(B|A) \in (\mathcal{L}|\mathcal{L})$.
- κ_1, κ_2 are *universally propositionally/conditionally revision equivalent w.r.t. $*$*
if $\kappa_1 * \mathcal{S} \cong \kappa_2 * \mathcal{S}$ for all $\mathcal{S} \subset \mathcal{L}$, resp. $\kappa_1 * \Delta \cong \kappa_2 * \Delta$ for all $\Delta \subset (\mathcal{L}|\mathcal{L})$.

Revision Equivalence

Let $*$ be an iterated revision operator for OCFs, taking (sets of) propositions resp. conditionals as input.

- κ_1, κ_2 are (*propositionally*) *revision equivalent* with respect to $*$ if $\kappa_1 * A \cong \kappa_2 * A$ for all $A \in \mathcal{L}$.
- κ_1, κ_2 are *conditionally revision equivalent* with respect to $*$ if $\kappa_1 * (B|A) \cong \kappa_2 * (B|A)$ for all $(B|A) \in (\mathcal{L}|\mathcal{L})$.
- κ_1, κ_2 are *universally propositionally/conditionally revision equivalent w.r.t. $*$* if $\kappa_1 * \mathcal{S} \cong \kappa_2 * \mathcal{S}$ for all $\mathcal{S} \subset \mathcal{L}$, resp. $\kappa_1 * \Delta \cong \kappa_2 * \Delta$ for all $\Delta \subset (\mathcal{L}|\mathcal{L})$.

Proposition: Downward Compatibility

- *Propositionally revision equivalent* ranking functions with respect to $*$ are (*inferentially*) *equivalent* if $*$ satisfies $\kappa * \varphi = \kappa$ if $\kappa \models \varphi$ (*Stability*).

Revision Equivalence

Let $*$ be an iterated revision operator for OCFs, taking (sets of) propositions resp. conditionals as input.

- κ_1, κ_2 are (*propositionally*) *revision equivalent* with respect to $*$ if $\kappa_1 * A \cong \kappa_2 * A$ for all $A \in \mathcal{L}$.
- κ_1, κ_2 are *conditionally revision equivalent* with respect to $*$ if $\kappa_1 * (B|A) \cong \kappa_2 * (B|A)$ for all $(B|A) \in (\mathcal{L}|\mathcal{L})$.
- κ_1, κ_2 are *universally propositionally/conditionally revision equivalent w.r.t. $*$* if $\kappa_1 * \mathcal{S} \cong \kappa_2 * \mathcal{S}$ for all $\mathcal{S} \subset \mathcal{L}$, resp. $\kappa_1 * \Delta \cong \kappa_2 * \Delta$ for all $\Delta \subset (\mathcal{L}|\mathcal{L})$.

Proposition: Downward Compatibility

- *Propositionally revision equivalent* ranking functions with respect to $*$ are (*inferentially*) *equivalent* if $*$ satisfies $\kappa * \varphi = \kappa$ if $\kappa \models \varphi$ (*Stability*).
- *Conditionally revision equivalent* ranking functions with respect to $*$ are *propositionally revision equivalent* with respect to $*$ equivalent if $*$ satisfies $\kappa * (A|\top) = \kappa * A$ for all $A \in \mathcal{L}$ and all κ (*Propositional Compatibility*).

Some Negative Results

Proposition

Let κ_1, κ_2 be two different, but (inferentially) equivalent ranking functions which both have **at least two layers** such that their **lowermost layer Ω_0 has more than one element**. Then there is a strategic c-revision operator $*_\sigma$ and $A \in \mathcal{L}$ such that $\kappa_1 *_\sigma A \not\equiv \kappa_2 *_\sigma A$.

Some Negative Results

Proposition

Let κ_1, κ_2 be two different, but (inferentially) equivalent ranking functions which both have **at least two layers** such that their **lowermost layer Ω_0 has more than one element**. Then there is a strategic c-revision operator $*_\sigma$ and $A \in \mathcal{L}$ such that $\kappa_1 *_\sigma A \not\equiv \kappa_2 *_\sigma A$.

Theorem

Let κ_1, κ_2 be two different ranking functions. Then κ_1, κ_2 are **conditionally revision equivalent** with respect to strategic c-revisions complying with (Stability) iff both κ_1, κ_2 have **exactly two layers Ω_0, Ω_1 such that $\Omega_0 = \{\omega_0\}$ contains exactly one element**.

Some Negative Results

Proposition

Let κ_1, κ_2 be two different, but (inferentially) equivalent ranking functions which both have **at least two layers** such that their **lowermost layer Ω_0 has more than one element**. Then there is a strategic c-revision operator $*_\sigma$ and $A \in \mathcal{L}$ such that $\kappa_1 *_\sigma A \not\equiv \kappa_2 *_\sigma A$.

Theorem

Let κ_1, κ_2 be two different ranking functions. Then κ_1, κ_2 are **conditionally revision equivalent** with respect to strategic c-revisions complying with (Stability) iff both κ_1, κ_2 have **exactly two layers Ω_0, Ω_1 such that $\Omega_0 = \{\omega_0\}$** contains exactly one element.

\implies Revision equivalence is not easy to achieve in general.
But we are not done yet!

How can we achieve Revision Equivalence?

We consider two approaches here.

How can we achieve Revision Equivalence?

We consider two approaches here.

Approach 1: Refine our Notion of Revision Equivalence

- Linear equivalence: $\kappa_2 = q \cdot \kappa_1$ instead of just $\kappa_1 \cong \kappa_2$
- Specific strategies for c-Revisions: $\sigma(r \cdot \kappa, \Delta) = r \cdot \sigma(\kappa, \Delta)$

How can we achieve Revision Equivalence?

We consider two approaches here.

Approach 1: Refine our Notion of Revision Equivalence

- Linear equivalence: $\kappa_2 = q \cdot \kappa_1$ instead of just $\kappa_1 \cong \kappa_2$
- Specific strategies for c-Revisions: $\sigma(r \cdot \kappa, \Delta) = r \cdot \sigma(\kappa, \Delta)$

Approach 2: Use TPO Revision Operators and Transformation Functions

When revising κ by φ , essentially “mimic” the behavior of a TPO revision operator.

Two options:

- Use a TPO revision operator \bullet directly: $\rho(\tau(\kappa) \bullet \varphi)$.
- Construct an OCF revision operator $*$ such that: $\tau(\kappa * \varphi) = \Psi \bullet \varphi$.

Linear Revision Equivalence

Definition: Linear Equivalence

Two OCFs κ_1, κ_2 over Ω are called *linearly equivalent* if $\kappa_2 = q \cdot \kappa_1$ for some positive rational number q .

Linear Revision Equivalence

Definition: Linear Equivalence

Two OCFs κ_1, κ_2 over Ω are called *linearly equivalent* if $\kappa_2 = q \cdot \kappa_1$ for some positive rational number q .

Theorem (Strategies for Linear Revision Equivalence)

If $\kappa_2 = q \cdot \kappa_1$, and σ is a selection strategy that satisfies

$$\sigma(r \cdot \kappa, \Delta) = r \cdot \sigma(\kappa, \Delta), \quad (\text{Mult}^c)$$

then $\kappa_2 *_{\sigma} \Delta = q \cdot (\kappa_1 *_{\sigma} \Delta)$ for any (consistent) set $\Delta = \{(B_1|A_1), \dots, (B_n|A_n)\}$.

Linear Revision Equivalence

Definition: Linear Equivalence

Two OCFs κ_1, κ_2 over Ω are called *linearly equivalent* if $\kappa_2 = q \cdot \kappa_1$ for some positive rational number q .

Theorem (Strategies for Linear Revision Equivalence)

If $\kappa_2 = q \cdot \kappa_1$, and σ is a selection strategy that satisfies

$$\sigma(r \cdot \kappa, \Delta) = r \cdot \sigma(\kappa, \Delta), \quad (\text{Mult}^c)$$

then $\kappa_2 *_\sigma \Delta = q \cdot (\kappa_1 *_\sigma \Delta)$ for any (consistent) set $\Delta = \{(B_1|A_1), \dots, (B_n|A_n)\}$.

Hence for strategic c-revisions $*_\sigma$ where the strategy σ satisfies (Mult^c) ...

Linear Revision Equivalence

Definition: Linear Equivalence

Two OCFs κ_1, κ_2 over Ω are called *linearly equivalent* if $\kappa_2 = q \cdot \kappa_1$ for some positive rational number q .

Theorem (Strategies for Linear Revision Equivalence)

If $\kappa_2 = q \cdot \kappa_1$, and σ is a selection strategy that satisfies

$$\sigma(r \cdot \kappa, \Delta) = r \cdot \sigma(\kappa, \Delta), \quad (\text{Mult}^c)$$

then $\kappa_2 *_\sigma \Delta = q \cdot (\kappa_1 *_\sigma \Delta)$ for any (consistent) set $\Delta = \{(B_1|A_1), \dots, (B_n|A_n)\}$.

Hence for strategic c-revisions $*_\sigma$ where the strategy σ satisfies (Mult^c) ...

- linearly equivalent ranking functions are (univ.) conditionally revision equivalent.

Linear Revision Equivalence

Definition: Linear Equivalence

Two OCFs κ_1, κ_2 over Ω are called *linearly equivalent* if $\kappa_2 = q \cdot \kappa_1$ for some positive rational number q .

Theorem (Strategies for Linear Revision Equivalence)

If $\kappa_2 = q \cdot \kappa_1$, and σ is a selection strategy that satisfies

$$\sigma(r \cdot \kappa, \Delta) = r \cdot \sigma(\kappa, \Delta), \quad (\text{Mult}^c)$$

then $\kappa_2 *_\sigma \Delta = q \cdot (\kappa_1 *_\sigma \Delta)$ for any (consistent) set $\Delta = \{(B_1|A_1), \dots, (B_n|A_n)\}$.

Hence for strategic c-revisions $*_\sigma$ where the strategy σ satisfies (Mult^c) ...

- linearly equivalent ranking functions are (univ.) conditionally revision equivalent.
- even the factor q is respected!

Preservation of Linear Equivalence

We can formalize this property of “respecting the factor” with the following definition.

Definition: Preservation of Linear Equivalence

A revision operator $*$ *preserves linear equivalence* if for any linearly equivalent κ_1, κ_2 such that $\kappa_2 = q \cdot \kappa_1$ and for any proper input φ , it holds that $\kappa_2 * \varphi = q \cdot (\kappa_1 * \varphi)$.

Preservation of Linear Equivalence

We can formalize this property of “respecting the factor” with the following definition.

Definition: Preservation of Linear Equivalence

A revision operator $*$ *preserves linear equivalence* if for any linearly equivalent κ_1, κ_2 such that $\kappa_2 = q \cdot \kappa_1$ and for any proper input φ , it holds that $\kappa_2 * \varphi = q \cdot (\kappa_1 * \varphi)$.

From the theorem on the previous slide we can conclude:

Strategic c-revisions $*_{\sigma}$ where the strategy σ satisfies (Mult^c) preserve linear equivalence under revision by sets of conditionals.

Revision Equivalence via TPO Revisions (1/2)

In principle, every revision operator \bullet for total preorders can be used to define a revision operator for ranking functions κ by utilizing the transformation functions τ and ρ .

Revision Equivalence via TPO Revisions (1/2)

In principle, every revision operator \bullet for total preorders can be used to define a revision operator for ranking functions κ by utilizing the transformation functions τ and ρ .

TPO Revision $\bullet \rightarrow$ OCF Revision \circledast

$$\kappa \circledast \varphi = \rho(\tau(\kappa) \bullet \varphi), \quad (1)$$

where φ is an appropriate input for \bullet .

Revision Equivalence via TPO Revisions (1/2)

In principle, every revision operator \bullet for total preorders can be used to define a revision operator for ranking functions κ by utilizing the transformation functions τ and ρ .

TPO Revision $\bullet \rightarrow$ OCF Revision \circledast

$$\kappa \circledast \varphi = \rho(\tau(\kappa) \bullet \varphi), \quad (1)$$

where φ is an appropriate input for \bullet .

Proposition

Let κ be an OCF, let \circledast be constructed from a revision operator \bullet for total preorders as described in (1), and let φ be an appropriate input for \bullet . Then the OCF-revision operator \otimes defined by

$$\kappa \otimes \varphi = (\kappa \circledast \varphi) \cdot \min\{\kappa(\omega) \mid \omega \in \Omega, \kappa(\omega) > 0\}$$

preserves linear equivalence.

Revision Equivalence via TPO Revisions (2/2)

OCF Revision * “mimics” TPO Revision ●

We define * accordingly from scratch such that

$$\tau(\kappa * \varphi) = \Psi \bullet \varphi \quad (2)$$

holds for every epistemic state Ψ properly represented by a total preorder, every $\kappa \in \tau^{-1}(\Psi)$, and every new information φ .

Revision Equivalence via TPO Revisions (2/2)

OCF Revision * “mimics” TPO Revision •

We define * accordingly from scratch such that

$$\tau(\kappa * \varphi) = \Psi \bullet \varphi \quad (2)$$

holds for every epistemic state Ψ properly represented by a total preorder, every $\kappa \in \tau^{-1}(\Psi)$, and every new information φ .

Proposition

Let * be a revision operator for ranking functions that satisfies (2) for some revision operator • for total preorders, and let φ be an appropriate input for •. Let κ_1, κ_2 be equivalent OCFs. Then

$$\kappa_1 * \varphi \cong \kappa_2 * \varphi.$$

Example: OCF Versions of Elementary Operators

Natural OCF-Revision

$$(\kappa *_n A)(\omega) = \begin{cases} 0 & \text{iff } \omega \models A \text{ and } \kappa(\omega) = \kappa(A), \\ 1 + \kappa(\omega) & \text{otherwise.} \end{cases}$$

Example: OCF Versions of Elementary Operators

Natural OCF-Revision

$$(\kappa *_n A)(\omega) = \begin{cases} 0 & \text{iff } \omega \models A \text{ and } \kappa(\omega) = \kappa(A), \\ 1 + \kappa(\omega) & \text{otherwise.} \end{cases}$$

Lexicographic OCF-Revision

$$(\kappa *_\ell A)(\omega) = \kappa(\omega) - \kappa(A) + \begin{cases} 0 & \text{iff } \omega \models A, \\ 1 + \max_{\omega \models A} \{\kappa(\omega)\} & \text{otherwise.} \end{cases}$$

Example: OCF Versions of Elementary Operators

Natural OCF-Revision

$$(\kappa *_{\textcolor{brown}{n}} A)(\omega) = \begin{cases} 0 & \text{iff } \omega \models A \text{ and } \kappa(\omega) = \kappa(A), \\ 1 + \kappa(\omega) & \text{otherwise.} \end{cases}$$

Lexicographic OCF-Revision

$$(\kappa *_{\textcolor{brown}{\ell}} A)(\omega) = \kappa(\omega) - \kappa(A) + \begin{cases} 0 & \text{iff } \omega \models A, \\ 1 + \max_{\omega \models A} \{\kappa(\omega)\} & \text{otherwise.} \end{cases}$$

Corollary

*Let κ_1, κ_2 be equivalent OCFs. Then κ_1 and κ_2 are (propositionally) revision equivalent with respect to both $*_{\textcolor{brown}{n}}$ and $*_{\textcolor{brown}{\ell}}$.*

Conclusion

Summary of Results

Conclusion

Summary of Results

- Formal definition of *revision equivalence* to study representation invariance under belief revision.

Conclusion

Summary of Results

- Formal definition of *revision equivalence* to study representation invariance under belief revision.
- Problem: Inserting *arbitrary* empty layers mostly breaks equivalence under DP-revision.

Conclusion

Summary of Results

- Formal definition of *revision equivalence* to study representation invariance under belief revision.
- Problem: Inserting *arbitrary* empty layers mostly breaks equivalence under DP-revision.
- Solution #1: Use strategic c-revisions satisfying (Mult^c) .

Conclusion

Summary of Results

- Formal definition of *revision equivalence* to study representation invariance under belief revision.
- Problem: Inserting *arbitrary* empty layers mostly breaks equivalence under DP-revision.
- Solution #1: Use strategic c-revisions satisfying (Mult^c) .
- Solution #2: Define OCF revisions that *mimic* TPO revisions.

Conclusion

Summary of Results

- Formal definition of *revision equivalence* to study representation invariance under belief revision.
- Problem: Inserting *arbitrary* empty layers mostly breaks equivalence under DP-revision.
- Solution #1: Use strategic c-revisions satisfying (Mult^c) .
- Solution #2: Define OCF revisions that *mimic* TPO revisions.

Future Work

Conclusion

Summary of Results

- Formal definition of *revision equivalence* to study representation invariance under belief revision.
- Problem: Inserting *arbitrary* empty layers mostly breaks equivalence under DP-revision.
- Solution #1: Use strategic c-revisions satisfying (Mult^c).
- Solution #2: Define OCF revisions that *mimic* TPO revisions.

Future Work

- Incorporate approaches to modularity/independence.

Conclusion

Summary of Results

- Formal definition of *revision equivalence* to study representation invariance under belief revision.
- Problem: Inserting *arbitrary* empty layers mostly breaks equivalence under DP-revision.
- Solution #1: Use strategic c-revisions satisfying (Mult^c).
- Solution #2: Define OCF revisions that *mimic* TPO revisions.

Future Work

- Incorporate approaches to modularity/independence.
- Evaluate more iterated revision frameworks (beyond Darwiche-Pearl).

Conclusion

Summary of Results

- Formal definition of *revision equivalence* to study representation invariance under belief revision.
- Problem: Inserting *arbitrary* empty layers mostly breaks equivalence under DP-revision.
- Solution #1: Use strategic c-revisions satisfying (Mult^c).
- Solution #2: Define OCF revisions that *mimic* TPO revisions.

Future Work

- Incorporate approaches to modularity/independence.
- Evaluate more iterated revision frameworks (beyond Darwiche-Pearl).
- Examine implications for improvement operators.