

# Introducing Defeasibility into Standpoint Logics

Nicholas Leisegang

University of Cape Town and CAIR

11 February 2025



# Introduction

In the late 1800's there was a court case in the US to determine whether tomatoes should be considered a fruit or a vegetable:

# Introduction

In the late 1800's there was a court case in the US to determine whether tomatoes should be considered a fruit or a vegetable:

- From a botanical perspective, tomatoes are fruits, and that fruits are vegetables.

# Introduction

In the late 1800's there was a court case in the US to determine whether tomatoes should be considered a fruit or a vegetable:

- From a botanical perspective, tomatoes are fruits, and that fruits are vegetables.
- From a culinary perspective, fruits and vegetables are classified according to whether they are savoury or sweet, and that they are *usually* distinct classes of food.

# Introduction

In the late 1800's there was a court case in the US to determine whether tomatoes should be considered a fruit or a vegetable:

- From a botanical perspective, tomatoes are fruits, and that fruits are vegetables.
- From a culinary perspective, fruits and vegetables are classified according to whether they are savoury or sweet, and that they are *usually* distinct classes of food.
- Tomatoes are *usually* savoury, but not always. (Eg. Tomatoes in a tomato pie)

# Introduction

In the late 1800's there was a court case in the US to determine whether tomatoes should be considered a fruit or a vegetable:

- From a botanical perspective, tomatoes are fruits, and that fruits are vegetables.
- From a culinary perspective, fruits and vegetables are classified according to whether they are savoury or sweet, and that they are *usually* distinct classes of food.
- Tomatoes are *usually* savoury, but not always. (Eg. Tomatoes in a tomato pie)
- The court case (legal perspective) sided with the culinary perspective. However, legally fruits and vegetables are considered *strictly* distinct.

# Introduction

In the late 1800's there was a court case in the US to determine whether tomatoes should be considered a fruit or a vegetable:

- From a botanical perspective, tomatoes are fruits, and that fruits are vegetables.
- From a culinary perspective, fruits and vegetables are classified according to whether they are savoury or sweet, and that they are *usually* distinct classes of food.
- Tomatoes are *usually* savoury, but not always. (Eg. Tomatoes in a tomato pie)
- The court case (legal perspective) sided with the culinary perspective. However, legally fruits and vegetables are considered *strictly* distinct.

NB

# Introduction

In the late 1800's there was a court case in the US to determine whether tomatoes should be considered a fruit or a vegetable:

- From a botanical perspective, tomatoes are fruits, and that fruits are vegetables.
- From a culinary perspective, fruits and vegetables are classified according to whether they are savoury or sweet, and that they are *usually* distinct classes of food.
- Tomatoes are *usually* savoury, but not always. (Eg. Tomatoes in a tomato pie)
- The court case (legal perspective) sided with the culinary perspective. However, legally fruits and vegetables are considered *strictly* distinct.

## NB

- Different perspectives disagree with each other.



# Introduction

In the late 1800's there was a court case in the US to determine whether tomatoes should be considered a fruit or a vegetable:

- From a botanical perspective, tomatoes are fruits, and that fruits are vegetables.
- From a culinary perspective, fruits and vegetables are classified according to whether they are savoury or sweet, and that they are *usually* distinct classes of food.
- Tomatoes are *usually* savoury, but not always. (Eg. Tomatoes in a tomato pie)
- The court case (legal perspective) sided with the culinary perspective. However, legally fruits and vegetables are considered *strictly* distinct.

## NB

- Different perspectives disagree with each other.
- Viewpoints can believe in rules that have exceptions.

## Goal

Construct a logical system that can represent multiple agents with:

- **External** contradictions between standpoints.
- Rules with exceptions, for **internal** contradictions within a standpoint.

## Goal

Construct a logical system that can represent multiple agents with:

- **External** contradictions between standpoints.
  - Rules with exceptions, for **internal** contradictions within a standpoint.
- 1 Combine standpoint logics (external contradictions) with KLM defeasible reasoning.

## Goal

Construct a logical system that can represent multiple agents with:

- **External** contradictions between standpoints.
- Rules with exceptions, for **internal** contradictions within a standpoint.

- 1 Combine standpoint logics (external contradictions) with KLM defeasible reasoning.
- 2 Describe syntax and semantics for **Defeasible Restricted Standpoint Logic** (DRSL).

## Goal

Construct a logical system that can represent multiple agents with:

- **External** contradictions between standpoints.
- Rules with exceptions, for **internal** contradictions within a standpoint.

- 1 Combine standpoint logics (external contradictions) with KLM defeasible reasoning.
- 2 Describe syntax and semantics for **Defeasible Restricted Standpoint Logic** (DRSL).
- 3 Create a version of (non-monotonic) entailment to reason with this logic.

## Goal

Construct a logical system that can represent multiple agents with:

- **External** contradictions between standpoints.
- Rules with exceptions, for **internal** contradictions within a standpoint.

- 1 Combine standpoint logics (external contradictions) with KLM defeasible reasoning.
- 2 Describe syntax and semantics for **Defeasible Restricted Standpoint Logic** (DRSL).
- 3 Create a version of (non-monotonic) entailment to reason with this logic.
- 4 Show that this system of reasoning can be described with an algorithm and a semantic structure.

Part of a broader project of integrating defeasible reasoning beyond the propositional case!  
(Eg. Description Logics, Modal Logics, First-Order Logic)

## Propositional KLM Logic [5]

The **language** for KLM defeasible reasoning consists of adding a rational consequence operator (defeasible implication) between Boolean expressions of the form,

$$\alpha \vdash \beta$$

which reads “ $\alpha$  *typically* implies  $\beta$ ”.



## Propositional KLM Logic [5]

The **language** for KLM defeasible reasoning consists of adding a rational consequence operator (defeasible implication) between Boolean expressions of the form,

$$\alpha \vdash \beta$$

which reads “ $\alpha$  *typically* implies  $\beta$ ”.

### Examples:

- $bird \vdash fly$ . “Birds typically fly”

## Propositional KLM Logic [5]

The **language** for KLM defeasible reasoning consists of adding a rational consequence operator (defeasible implication) between Boolean expressions of the form,

$$\alpha \vdash \beta$$

which reads “ $\alpha$  *typically* implies  $\beta$ ”.

### Examples:

- $bird \vdash fly$ . “Birds typically fly”
- $(tomato \vdash veg) \wedge (veg \vdash \neg fruit)$ . “Tomatoes are usually considered vegetables, and vegetables are usually not fruits.”

$$\mathcal{K} = \{penguin \rightarrow bird, bird \sim fly, penguin \sim \neg fly\}$$

$$\mathcal{K} = \{penguin \rightarrow bird, bird \sim fly, penguin \sim \neg fly\}$$

## Definition [1, 6]

A **ranking function** is a function  $R : \mathcal{U} \rightarrow \mathbb{N} \cup \{\infty\}$ , where  $\mathcal{U}$  is the set of classical valuations over a set of atoms, such that if  $R(u) < \infty$ , then for every  $0 \leq j < R(u)$  there exists  $v \in \mathcal{U}$  such that  $R(v) = j$ .

$$\mathcal{K} = \{penguin \rightarrow bird, bird \sim fly, penguin \sim \neg fly\}$$

## Definition [1, 6]

A **ranking function** is a function  $R : \mathcal{U} \rightarrow \mathbb{N} \cup \{\infty\}$ , where  $\mathcal{U}$  is the set of classical valuations over a set of atoms, such that if  $R(u) < \infty$ , then for every  $0 \leq j < R(u)$  there exists  $v \in \mathcal{U}$  such that  $R(v) = j$ .

$\infty$	$\overline{pbf}, \overline{pbf}$
2	$pbf$
1	$pbf, \overline{pbf}$
0	$\overline{pbf}, pbf, \overline{pbf}$

$$\mathcal{K} = \{penguin \rightarrow bird, bird \sim fly, penguin \sim \neg fly\}$$

## Definition [1, 6]

A **ranking function** is a function  $R : \mathcal{U} \rightarrow \mathbb{N} \cup \{\infty\}$ , where  $\mathcal{U}$  is the set of classical valuations over a set of atoms, such that if  $R(u) < \infty$ , then for every  $0 \leq j < R(u)$  there exists  $v \in \mathcal{U}$  such that  $R(v) = j$ .

$\infty$	$p\bar{b}\bar{f}, p\bar{b}\bar{f}$
2	$pbf$
1	$p\bar{b}\bar{f}, \bar{p}b\bar{f}$
0	$\bar{p}b\bar{f}, p\bar{b}f, p\bar{b}\bar{f}$

- Intuitively,  $\bar{p}b\bar{f}$  is “more typical” than  $p\bar{b}\bar{f}$ .

$$\mathcal{K} = \{penguin \rightarrow bird, bird \sim fly, penguin \sim \neg fly\}$$

## Definition [1, 6]

A **ranking function** is a function  $R : \mathcal{U} \rightarrow \mathbb{N} \cup \{\infty\}$ , where  $\mathcal{U}$  is the set of classical valuations over a set of atoms, such that if  $R(u) < \infty$ , then for every  $0 \leq j < R(u)$  there exists  $v \in \mathcal{U}$  such that  $R(v) = j$ .

$\infty$	$p\bar{b}f, p\bar{b}\bar{f}$
2	$pbf$
1	$p\bar{b}f, \bar{p}b\bar{f}$
0	$\bar{p}bf, pbf, \bar{p}\bar{b}f$

- Intuitively,  $\bar{p}bf$  is “more typical” than  $p\bar{b}f$ .
- Rank  $\infty$  are “impossible” states (They break strict rules).

$$\mathcal{K} = \{penguin \rightarrow bird, bird \sim fly, penguin \sim \neg fly\}$$

## Definition [1, 6]

A **ranking function** is a function  $R : \mathcal{U} \rightarrow \mathbb{N} \cup \{\infty\}$ , where  $\mathcal{U}$  is the set of classical valuations over a set of atoms, such that if  $R(u) < \infty$ , then for every  $0 \leq j < R(u)$  there exists  $v \in \mathcal{U}$  such that  $R(v) = j$ .

$\infty$	$\overline{pbf}, \overline{pbf}$
2	$pbf$
1	$pbf, \overline{pbf}$
0	$\overline{pbf}, pbf, \overline{pbf}$

- Intuitively,  $\overline{pbf}$  is “more typical” than  $pbf$ .
- Rank  $\infty$  are “impossible” states (They break strict rules).
- Here,  $bird \sim fly$  follows from the table since in the lowest rank where  $bird$  is true, we have that  $bird \rightarrow fly$ .



- In the context of KLM defeasible reasoning, there are several different notions of non-monotonic entailment from a knowledge base  $\mathcal{K}$ .
- We focus on **Rational Closure** [6], which is often considered one of the most fundamental notions of non-monotonic entailment in KLM-style reasoning.

- In the context of KLM defeasible reasoning, there are several different notions of non-monotonic entailment from a knowledge base  $\mathcal{K}$ .
- We focus on **Rational Closure** [6], which is often considered one of the most fundamental notions of non-monotonic entailment in KLM-style reasoning.
- Semantically, rational closure corresponds to the point-wise minimum ranking function which satisfies  $\mathcal{K}$  [3] i.e.  $r_{RC}(u) \leq r(u)$  for any valuation  $u$  and any ranking function which satisfies  $\mathcal{K}$ .

- In the context of KLM defeasible reasoning, there are several different notions of non-monotonic entailment from a knowledge base  $\mathcal{K}$ .
- We focus on **Rational Closure** [6], which is often considered one of the most fundamental notions of non-monotonic entailment in KLM-style reasoning.
- Semantically, rational closure corresponds to the point-wise minimum ranking function which satisfies  $\mathcal{K}$  [3] i.e.  $r_{RC}(u) \leq r(u)$  for any valuation  $u$  and any ranking function which satisfies  $\mathcal{K}$ .
- Then, if  $r_{RC}$  entails  $\alpha \sim \beta$ , we write  $\mathcal{K} \models_{RC} \alpha \sim \beta$ .

- In the context of KLM defeasible reasoning, there are several different notions of non-monotonic entailment from a knowledge base  $\mathcal{K}$ .
- We focus on **Rational Closure** [6], which is often considered one of the most fundamental notions of non-monotonic entailment in KLM-style reasoning.
- Semantically, rational closure corresponds to the point-wise minimum ranking function which satisfies  $\mathcal{K}$  [3] i.e.  $r_{RC}(u) \leq r(u)$  for any valuation  $u$  and any ranking function which satisfies  $\mathcal{K}$ .
- Then, if  $r_{RC}$  entails  $\alpha \sim \beta$ , we write  $\mathcal{K} \approx_{RC} \alpha \sim \beta$ .
- Given  $\mathcal{K}$  and  $\alpha \sim \beta$ , there is an equivalent algorithm which determines whether  $\mathcal{K} \approx_{RC} \alpha \sim \beta$ . The complexity of this is  $P^{NP}$ . [2, 6]

## Propositional Standpoint Logic [4]

The language of **propositional standpoint logic** is a multi-modal logic where the modal operators are indexed by a set of standpoint symbols  $\mathcal{S}$  representing agents:

$\Box_s \phi = \text{“it is unequivocal to } s \text{ that } \phi\text{”}$      $\Diamond_s \phi = \text{“it is possible to } s \text{ that } \phi\text{”}$

We also include **standpoint sharpening statements** of the form  $s_1 \preceq s_2$  which intuitively expresses that  $s_1$  is a “more specific” standpoint to  $s_2$ .

## Propositional Standpoint Logic [4]

The language of **propositional standpoint logic** is a multi-modal logic where the modal operators are indexed by a set of standpoint symbols  $\mathcal{S}$  representing agents:

$\Box_s \phi =$  “it is unequivocal to  $s$  that  $\phi$ ”     $\Diamond_s \phi =$  “it is possible to  $s$  that  $\phi$ ”

We also include **standpoint sharpening statements** of the form  $s_1 \preceq s_2$  which intuitively expresses that  $s_1$  is a “more specific” standpoint to  $s_2$ .

### Examples:

- $\Box_B(\text{tomato} \rightarrow (\text{fruit} \vee \text{veg}))$ . “It is unequivocal to  $B$  that tomatoes are fruit or veg.”

## Propositional Standpoint Logic [4]

The language of **propositional standpoint logic** is a multi-modal logic where the modal operators are indexed by a set of standpoint symbols  $\mathcal{S}$  representing agents:

$\Box_s \phi =$  “it is unequivocal to  $s$  that  $\phi$ ”     $\Diamond_s \phi =$  “it is possible to  $s$  that  $\phi$ ”


We also include **standpoint sharpening statements** of the form  $s_1 \preceq s_2$  which intuitively expresses that  $s_1$  is a “more specific” standpoint to  $s_2$ .

### Examples:

- $\Box_B(\text{tomato} \rightarrow (\text{fruit} \vee \text{veg}))$ . “It is unequivocal to  $B$  that tomatoes are fruit or veg.”
- $\Diamond_A(\text{fruit} \wedge \text{veg})$ . “According to  $A$ , it is possible for something to be both a fruit and vegetable.”

# Standpoint Logics: Semantics


The semantics are given by a triple  $M = (\Pi, \sigma, \gamma)$ : [4]





# Standpoint Logics: Semantics

The semantics are given by a triple  $M = (\Pi, \sigma, \gamma)$ : [4]




Each  $\pi \in \Pi$  is a precise viewpoint where everything is fixed.

The map  $\gamma$  assigns a classical valuation to each  $\pi$ .

The map  $\sigma$  assigns a set of possible “precisifications” to each standpoint.

# Standpoint Logics: Semantics

The semantics are given by a triple  $M = (\Pi, \sigma, \gamma)$ : [4]



Each  $\pi \in \Pi$  is a precise viewpoint where everything is fixed.

The map  $\gamma$  assigns a classical valuation to each  $\pi$ .

The map  $\sigma$  assigns a set of possible “precisifications” to each standpoint.

Variation of a multi-modal S5.

# Example

Two agents, A and B:


- $\Box_A(\text{tomato} \rightarrow \text{fruit})$ . “Tomatoes are fruits.”
- $\Diamond_A(\text{fruit} \wedge \text{veg})$ . “It is possible for a fruit to be a vegetable.”
- $\Box_B(\text{tomato} \rightarrow (\text{fruit} \vee \text{veg}))$ . “Tomatoes are fruit or veg.”
- $\Box_B(\text{fruit} \rightarrow \neg \text{veg})$ . “Fruits and veg are distinct.”

# Example

Two agents, A and B:

- $\Box_A(\text{tomato} \rightarrow \text{fruit})$ . “Tomatoes are fruits.”
- $\Diamond_A(\text{fruit} \wedge \text{veg})$ . “It is possible for a fruit to be a vegetable.”
- $\Box_B(\text{tomato} \rightarrow (\text{fruit} \vee \text{veg}))$ . “Tomatoes are fruit or veg.”
- $\Box_B(\text{fruit} \rightarrow \neg \text{veg})$ . “Fruits and veg are distinct.”

Model:



## Language of DRSL

We allow statements of the form

$$\psi ::= \alpha \mid \alpha \sim \beta \mid \Box_s \psi \mid \Diamond_s \psi \mid \psi \wedge \psi \quad \text{or} \quad e ::= s \preceq t$$

where  $\alpha, \beta$  are Boolean formulas and  $s$  and  $t$  are standpoint symbols.

## Language of DRSL

We allow statements of the form

$$\psi ::= \alpha \mid \alpha \sim \beta \mid \Box_s \psi \mid \Diamond_s \psi \mid \psi \wedge \psi \quad \text{or} \quad e ::= s \preceq t$$

where  $\alpha, \beta$  are Boolean formulas and  $s$  and  $t$  are standpoint symbols.

Extends propositional standpoint logic by allowing agents to hold *defeasible* beliefs.

# Example

## Going back to our motivating example:

- Botanical perspective: tomatoes are fruits; fruits are veg.

# Example

## Going back to our motivating example:

- Botanical perspective: tomatoes are fruits; fruits are veg.

$$\{\Box_B(\textit{tomato} \rightarrow \textit{fruit}), \Box_B(\textit{fruit} \rightarrow \textit{veg})\}$$



## Going back to our motivating example:

- Botanical perspective: tomatoes are fruits; fruits are veg.

$$\{\Box_B(\textit{tomato} \rightarrow \textit{fruit}), \Box_B(\textit{fruit} \rightarrow \textit{veg})\}$$

- Culinary perspective: fruits and vegetables are classified according to whether they are savoury or sweet, and they are *usually* distinct; tomatoes are *usually* savoury.

## Going back to our motivating example:

- Botanical perspective: tomatoes are fruits; fruits are veg.

$$\{\Box_B(\text{tomato} \rightarrow \text{fruit}), \Box_B(\text{fruit} \rightarrow \text{veg})\}$$

- Culinary perspective: fruits and vegetables are classified according to whether they are savoury or sweet, and they are *usually* distinct; tomatoes are *usually* savoury.

$$\{\Box_C(\text{fruit} \leftrightarrow \text{sweet}), \Box_C(\text{veg.} \leftrightarrow \text{sav.}), \Box_C(\text{fruit} \sim \neg \text{veg}), \\ \Box_C(\text{tomato} \sim \text{sav.})\}$$

## Going back to our motivating example:

- Botanical perspective: tomatoes are fruits; fruits are veg.

$$\{\Box_B(\text{tomato} \rightarrow \text{fruit}), \Box_B(\text{fruit} \rightarrow \text{veg})\}$$

- Culinary perspective: fruits and vegetables are classified according to whether they are savoury or sweet, and they are *usually* distinct; tomatoes are *usually* savoury.

$$\{\Box_C(\text{fruit} \leftrightarrow \text{sweet}), \Box_C(\text{veg.} \leftrightarrow \text{sav.}), \Box_C(\text{fruit} \sim \neg \text{veg}), \\ \Box_C(\text{tomato} \sim \text{sav.})\}$$

- Legal perspective: agrees with  $C$ , but fruits are *strictly* not veg.

## Going back to our motivating example:

- Botanical perspective: tomatoes are fruits; fruits are veg.

$$\{\Box_B(\text{tomato} \rightarrow \text{fruit}), \Box_B(\text{fruit} \rightarrow \text{veg})\}$$

- Culinary perspective: fruits and vegetables are classified according to whether they are savoury or sweet, and they are *usually* distinct; tomatoes are *usually* savoury.


$$\{\Box_C(\text{fruit} \leftrightarrow \text{sweet}), \Box_C(\text{veg.} \leftrightarrow \text{sav.}), \Box_C(\text{fruit} \sim \neg \text{veg}), \\ \Box_C(\text{tomato} \sim \text{sav.})\}$$

- Legal perspective: agrees with  $C$ , but fruits are *strictly* not veg.

$$\{L \preceq C, \Box_L(\text{fruit} \rightarrow \neg \text{veg})\}$$


# Defeasible Restricted Standpoint Logic: Semantics

Looks very similar to the propositional case:



# Defeasible Restricted Standpoint Logic: Semantics


Looks very similar to the propositional case:



We just have a **ranking function** instead of a classical valuation.


# Rational Closure Algorithm for DRSL

**We split a DRSL knowledge base into several propositional KLM ones:**



# Rational Closure Algorithm for DRSL


We use this to check entailment:





# Rational Closure Algorithm for DRSL

We use this to check entailment:




## Theorem

The above algorithm is in  $P^{NP}$ , the same as entailment checking for propositional Rational Closure.


# Semantics for Rational Closure

This Rational Closure can also be constructed using a single semantic structure. Using our motivating example:



# Semantics for Rational Closure

This Rational Closure can also be constructed using a single semantic structure. Using our motivating example:



We can use this to check conclusions like “ $\Box_{All}(tomato \sim veg)$ ”!

# Conclusion

- Proposed the language and semantics of DRSL to handle multiple standpoints who hold defeasible beliefs.

- Proposed the language and semantics of DRSL to handle multiple standpoints who hold defeasible beliefs.
- Constructed a notion of (non-monotonic) entailment that extends Rational Closure from the propositional case.

- Proposed the language and semantics of DRSL to handle multiple standpoints who hold defeasible beliefs.
- Constructed a notion of (non-monotonic) entailment that extends Rational Closure from the propositional case.
- **Main Result 1:** Rational Closure has an equivalent definition using an algorithm or a single semantic model.

- Proposed the language and semantics of DRSL to handle multiple standpoints who hold defeasible beliefs.
- Constructed a notion of (non-monotonic) entailment that extends Rational Closure from the propositional case.
- **Main Result 1:** Rational Closure has an equivalent definition using an algorithm or a single semantic model.
- **Main Result 2:** Entailment checking is computable in  $P^{NP}$ . Complexity is the same as in the propositional case!



- ① Develop a representation result with KLM-style postulates which capture the semantics.
- ② Analyze different notions of entailment. (Eg. lexicographic closure, c-inference)
- ③ Belief revision in standpoint logics: How does it look when agents change their beliefs based on each other's beliefs?

# Thank you!



CASINI, G., MEYER, T., AND VARZINCZAK, I.

Taking defeasible entailment beyond rational closure.

In *Logics in Artificial Intelligence* (Cham, 2019), F. Calimeri, N. Leone, and M. Manna, Eds., Springer International Publishing, pp. 182–197.



FREUND, M.

Preferential reasoning in the perspective of Poole default logic.

*Artificial Intelligence* 98, 1 (1998), 209–235.



GIORDANO, L., GLIOZZI, V., OLIVETTI, N., AND POZZATO, G.

Semantic characterization of rational closure: From propositional logic to description logics.

*Artificial Intelligence* 226 (2015), 1–33.



GÓMEZ ÁLVAREZ, L., AND RUDOLPH, S.

Standpoint logic: Multi-perspective knowledge representation.

In *Proceedings of the 12th International Conference (FOIS 2021) Frontiers in Artificial Intelligence and Applications* (2021), vol. 3344 of *Frontiers in Artificial Intelligence and Applications*, IOS Press, pp. 3 – 17.



KRAUS, S., LEHMANN, D., AND MAGIDOR, M.

Nonmonotonic reasoning, preferential models and cumulative logics.

*Artificial intelligence* 44, 1-2 (1990), 167–207.



LEHMANN, D., AND MAGIDOR, M.

What does a conditional knowledge base entail?

*Artificial intelligence* 55, 1 (1992), 1–60.